

DaimlerChrysler AG

REPLACED BY  
ART 3:ANDTDevice for controlling an engine or transmission

5 The invention relates to a device for controlling an  
engine and/or transmission having a control device  
which is arranged remotely from the engine/transmission  
and which provides the open-loop and closed-loop  
control algorithms, and a unit which is electrically  
10 conductively connected directly to a plurality of  
sensors and which is attached to the  
engine/transmission, wherein the unit has an A/D  
converter for converting the sensor signals originating  
from the sensors into digital sensor signals, and the  
15 digital sensor signals are converted to data bus  
signals by means of a data bus transceiver unit in  
order to be able to communicate via a data bus between  
the unit and the control device which is arranged  
remotely therefrom.

20

EP 0 758 726 A2 and DE 100 36 601 A1 have each  
disclosed a controller for a motor vehicle having an  
automatic transmission. The control device with the  
open-loop/closed-loop control algorithm for the  
25 transmission is attached to the transmission as an add-  
on control device. Sensors and actuators which are each  
arranged inside the transmission are connected to the  
control device via a plug. Since the control device is  
installed on the transmission, it must be both heat-  
30 resistant and protected against soiling, requiring an  
increased level of complexity. In addition, during  
manufacture and while the transmission is being  
assembled it is necessary in each case to provide a  
matching control device for the transmission. For an  
35 alternative transmission for the same motor vehicle in  
which more sensors are used it is necessary for a  
control device which has been changed in hardware terms  
to be installed on the transmission. As a result,

whenever changes are made to the transmission the control device hardware must also be changed.

DE 199 63 610 A1 discloses a data bus system with  
5 control devices for motor vehicles, with each control  
device being divided into an operations control  
function and an I/O processing function. Each function  
is assigned a separate microcontroller here and in each  
10 case one operations control function and one I/O  
processing function form together one control device.  
In the case of means of transportation with  
transmission variants it is therefore necessary for the  
control device to be matched each time to the other  
transmission variant, which leads to a high level of  
15 expenditure.

DE 199 48 969 A1 discloses a control apparatus for a  
vehicle drive train composed of an engine and  
transmission. A first control device which is arranged  
20 remotely from the transmission and a second  
transmission control device which is provided on the  
transmission are provided. Electronic components with a  
high power loss, in particular output stages, are  
installed in the transmission control device which has  
25 to be of heat-resistant design because it is attached  
to the transmission. Both control devices have at least  
one microcomputer, memory and output stages for  
actuating sensors and actuators. The microcomputer runs  
software for implementing open-loop and closed-loop  
30 control algorithms and carries out sensor signal  
conditioning. Since the sensors and actuators have to  
be arranged directly on the transmission control  
device, only a small number of assemblies or vehicle  
variants is covered with one version of the control  
35 device. For different engine types and series in the  
case of motor vehicles, this means that a control  
device with different interfaces for sensors has to be  
developed in each case for petrol or diesel variants or

different numbers of cylinders. In addition, a new control device has to be developed in order to increase the computing power and to carry out additional functionalities for the conventional control device  
5 concepts.

When the control devices are installed on the drive train, for example on the engine or on the transmission, the temperature load for the electronic  
10 components provided there, in particular for the increasingly complex microcomputers and memories, is very high, and entails additional costs for the qualification of the components for the assembly-specific ambient temperatures. If the respective  
15 control device is arranged remotely from the assemblies, for example the transmission, an extensive amount of cabling has previously been necessary between the assemblies and control devices in order to connect the sensors and actuators.

20 The present invention is based on the object of providing a device for controlling an engine/transmission with a control device which is arranged remotely from the engine/transmission, with  
25 the expenditure in terms of cabling for the sensors and actuators on the assembly being reduced. A further object of the present invention is to provide the electronic connection of the sensors and actuators on the control device in such a way that only a small  
30 number of control device variants is necessary for the various drive train variants with the different sensors and actuators.

The object is achieved according to the invention by  
35 means of the features of claim 1. According to said claim, a plurality of control devices are embodied with a uniform data bus transceiver unit, to each of which an assembly data bus is connected, the unit is embodied

- as an assembly-specific sensor/actuator interface with a plurality of parallel connections for the sensors/actuators and a connection for the assembly data bus, and a signal converter is provided for
5. converting the sensor signals of a plurality of sensors into the data bus signal so that, for designs of the device with different assembly variants with different sensors/actuators, it is possible to use the same control device without changing the hardware of its
- 10 sensor/actuator connection. The signal converter also converts the sensor signals directly into the data bus signals in accordance with an open-loop/closed-loop control algorithm without the intermediate connection of a calculation, and the sensor/actuator interface is
- 15 designed for series means of transportation with a plurality of engine/transmission variants in at least two designs, with said designs differing in the number of sensor connections provided.
- 20 The assembly data bus has a serial data transmission in digital form with real-time-specific peripheral conditions, it being possible for said data bus to be of electrical or optical design. The assembly data bus permits synchronous data transmission of the sensor
- 25 signals. The assembly-specific sensor/actuator interfaces are connected to the assembly data bus. In addition, the assembly data bus is connected to a standardized data bus transceiver unit of the control devices.
- 30
- 35 In addition to the assembly data bus it is possible to arrange a further vehicle data bus between the control devices, said further vehicle data bus being routed in the passenger compartment of the vehicle. Messages are exchanged directly between the control devices via the vehicle data bus and signals are transmitted by assemblies which are arranged remotely from the assembly to be controlled. For example, signals are

REPLACED BY  
ART 34 PART

transmitted from the exhaust gas sensor system, fuel  
tank venting system and the like to the engine control  
device, processed there in a control algorithm and  
transmitted via the assembly data bus to the sensor  
5 actuator interface in the motor and/or transmission.  
Data bus is understood in this context to mean a medium  
which can transmit digital signals. Conventional binary  
high signals or low signals or even a pulse-width  
modulation can be carried out by means of the data bus  
10 here.

The control devices are of standardized design so that  
a plurality of control devices have the same interface  
for the assembly data bus. The internal design of the  
15 control device may be standardized with respect to  
microcomputers, memories and housings. This has the  
advantage that open-loop and closed-loop control  
algorithms are carried out by application software,  
while the control devices have matching hardware. This  
20 results in a considerable cost advantage when complex  
systems are built up.

The control device which is arranged remotely from the  
assembly, i.e. engine and/or transmission, comprises in  
25 each case a powerful microcomputer and a corresponding  
software, it being possible for the latter to be  
composed of individual software modules. Each  
alternative transmission or engine type is then  
assigned a matching software module. After the software  
30 has been input into the control device, the software  
carries out the open-loop/closed-loop control  
algorithms for the engine/transmission unit. The  
control device which is arranged remotely from the  
assembly is connected in an electrically conductive  
35 fashion to the sensor/actuator interface via a data bus  
line. The data bus signals are decomposed by the signal  
converter in the control device and in the  
sensor/actuator interface, and the individual

components are assigned to the various sensors and actuators. In addition, the individual signals are converted in the sensor/actuator interface so that they can both control the actuators arranged in the transmission or engine as analog signals and the sensor signals are also digitized in the opposite direction and converted into the data bus signal so that they can be processed further in the control device which is arranged remotely.

10

In one development of the invention, the unit is embodied as an assembly-specific sensor/actuator interface with a plurality of parallel connections for the sensors/actuators and a connection for the assembly data bus, and a signal converter is provided for converting the sensor signals of a plurality of sensors into the data bus signal so that for embodiments of the device for different assembly variants with different sensors/actuators it is possible to use the same control device without hardware modification of its sensor/actuator connection, and a control device is integrated into the housing of the gear selector lever for shifting gear speeds or for shifting an automatic transmission.

25

In one development of the invention a plurality of standard control devices which are independent of assemblies and which have standardized interfaces with the sensor/actuator interface and with the rest of the surroundings of the vehicle are provided. In the context, the assembly-specific aspects are moved to the sensor/actuator interface. Aspects which are independent of the assemblies are assigned to the standardized assembly control device. The sensor/actuator interface and the assembly control device are connected to one another via a standardized interface, i.e. via the data bus transceiver unit. The assembly-specific sensor/actuator interface preferably

35

provides a means for converting signals, preparing signals, in particular closed-loop control near to the actuators as well as, for example, basic engine functions for providing emergency functions.

5

Connections for sensors such as the engine speed, crankshaft speed or temperature of the transmission and connections for actuators such as injection valves, ignition coils and switching valves are provided at the  
10 sensor/actuator interface. Pedal value signal transmitters, a charger probe, an exhaust gas temperature sensor and connections for actuators such as clutch switches, starter relays, fuel pumps or fuel tank venting valves are connected either directly to a  
15 control device or connected via a sensor/actuator interface to a vehicle data bus. The assembly-specific sensors and actuators are connected to the sensor/actuator interface. With respect to the engine, it is also possible to provide sensors such as a  
20 knocking sensor, a crankshaft/camshaft rotation speed sensor, an air mass flowmeter and actuators such as throttle valves, swirl valves and exhaust gas valves, ignition coils and injection valves. The sensor/actuator interface is arranged directly on the  
25 assembly, i.e. on the transmission or on the engine. The sensors are provided on the outside or inside of the assembly.

The sensor/actuator interface is, as it were, a  
30 distributor between the various sensors and actuators and converts the sensed signals into data bus signals so that the signals can be transmitted via the data bus sequentially, i.e. using a time-division multiplex method, or in parallel with a frequency-division  
35 multiplex method. Apart from the sensing of signals and the operation of actuators, the sensor/actuator interface can also carry out preprocessing of signals and storage of adaptation parameters. However, the

REPLACED BY  
ART 34 AMDT

sensor/actuator interface does not carry out any open-loop/closed-loop control algorithm calculations but instead merely transmits the sensor and actuator signals via the assembly data bus to the control device  
5 which is arranged remotely where the complex control algorithms are then carried out.

The major advantage of the present invention is that only the sensor/actuator interface has to be adapted  
10 for different assembly variants, for example petrol or diesel engines with different numbers of cylinders, different transmissions with different gear speeds and differing clutches. The remotely arranged control device can remain essentially unchanged in terms of its  
15 hardware, while all that is necessary is to input other software modules into the control device.

When there are a greater number of sensors, a sensor/actuator interface with a greater number of  
20 connections is then provided, with the data bus protocol remaining unchanged so that only a greater number of messages are transmitted via the assembly data bus. As a result, one standard control device can be provided for a predefined number of assembly  
25 variants. In the field of motor vehicle manufacture or aircraft manufacture this leads to the considerable advantage that it is not necessary to produce a new control device for each assembly variant. Only the sensor/actuator interface, as it were the adapter or  
30 multiple plug, for the sensors and actuators is changed. The complex microcomputers with the closed-loop and open-loop control algorithms are not provided in the sensor/actuator interface and accordingly also do not need to be adapted with a high degree of  
35 expenditure.

As a result of the separation of the control device as a closed-loop and open-loop control unit and the



REF ID: A61461  
ART 34/440T

sensor/actuator interface for the assembly-specific sensor system and actuator system it is possible for the control device with the highly integrated semiconductors such as microcomputers and memories to  
5 be located in the vehicle at an installation location which is loaded less in terms of environmental influences, for example in the footwell of the front seat passenger. As a result, with the highly integrated semiconductors there are cost and quality advantages  
10 over the current solution where a control device with microcomputer is installed directly on the assembly.

The sensor/actuator interface can be configured easily, in terms of cost and quality criteria, for the rough  
15 operating conditions in the engine compartment and on the assembly. The sensor/actuator interface can be embodied with a small number of printed circuit board layers, simpler ceramic substrates such as thick-film ceramic,  $Al_2O_3$  and less complex modules than is the case  
20 with the control devices used on the assembly in the past. The smaller complexity of the sensor/actuator interface permits the dissipated heat to be conducted away better, in particular from the power semiconductors and makes higher permissible operating  
25 temperatures possible as well as providing improved robustness with respect to environmental influences. Furthermore, a small number of sensors and actuators can already be integrated in the sensor/actuator interface. As a result of the greater degree of  
30 robustness of the sensor/actuator interface in comparison with a control unit, more free spaces are obtained when locating the sensors and actuators on the assembly itself. The sensor/actuator interface can therefore be used for optimized placing with respect to  
35 the assembly cable set.

The sensor/actuator interface has a storage means in which the digital sensor signals can be buffered and

where the sensor signals are converted in terms of the predefined value range and/or standardization of the signals to a predefined numerical range, the data bus transceiver unit reading out the digital sensor signals from the storage means and converting them into data bus signals which can then be transmitted to the control device via the assembly data bus. The conversion into the data bus signals at the sensor/actuator interface can be carried out, for example, into the known data bus protocols, for example CAN, LIN, Firewire, Bluetooth, USB, pulse width modulation and also other modulated signals such as frequency modulation or amplitude modulation. In order to convert into the predefined value range and in order to diagnose whether the sensor or actuator carries out its functions it is possible to provide a very small robust microcomputer so that when the control device fails or when there are interface problems the safety and availability of the sensor and actuator signal transmission is then ensured, for example, by means of an emergency transmission path. However, the sensor/actuator interface also differs from the control devices provided in the fitting solution in that no open-loop and closed-loop control algorithms are provided for the sensors and actuators. A pure hardware solution can be provided for a particularly fast conversion of the sensor signals into data bus signals.

In one particularly preferred development of the sensor/actuator interface for production vehicles such as ships, aircraft and motor vehicles, there are at least two embodiments of each type, each differing in the number of sensor/actuator connections provided. In certain production vehicles it is not necessary for all the connections of the sensor/actuator interface to be assigned but instead the sensor/actuator interface is configured in such a way that it can be used even when certain connections are not assigned. As a result a

very small number of variants of the sensor/actuator interface and of the associated control devices is produced even though there can be a large number of different assembly variants. It is then not necessary to provide new connections for new sensors and actuators on the control device every time but instead only one data bus connection to the sensor/actuator interface for each variant. The number of variants ultimately affects the data bus messages to be transmitted. The individual sensor signals are usually transmitted sequentially by means of an asynchronous or synchronous data bus protocol to the control device and evaluated there in their chronological sequence. The closed-loop control algorithms are then applied by the control device and the control signals for the actuators are transmitted again via the assembly data bus to the sensor/actuator interface and converted there in such a way that the actuators can be actuated.

It is also possible to switch a plurality of sensor/actuator interfaces in parallel or in cascades so that one sensor/actuator interface can be arranged on the engine and one sensor/actuator interface can be arranged on the transmission. The control device can then have, for example, two data bus connections which are connected in an electrically conductive fashion to the different sensor/actuator interfaces.

In another development of the invention, the transmission control device is integrated into the housing of the automatic transmission or gear speed selector lever of the means of transportation. If appropriate, the entire transmission control system including a sensor/actuator interface can be integrated into the selector lever. This makes sense in particular in rear-wheel drive vehicles because of the direct proximity of the transmission and gear selector lever.

The control apparatus can also be arranged in conjunction with assemblies such as clutches, starter generators or drives in the field of utility vehicle engineering, marine engineering or aircraft  
5 engineering. In addition, according to the present invention the sensor/actuator interface can also be used in hybrid vehicles or hydrogen-powered vehicles.

A further advantage of the present invention is that a  
10 diagnosis or test phase, for example during the manufacture of vehicles, is simplified. Instead of connecting the sensor/actuator interface to the control device it can be connected directly to a diagnostic device or test device which models the control device  
15 in various test phases. In particular, workshop and test bench computers may be connected to the production line to the sensor/actuator interfaces or to the assembly data bus. Alternatively, what is referred to as a hardware-in-the-loop method can be carried out.  
20 The sensor/actuator interface permits simple connection of the test devices which then make available the necessary test signals for the test operation. For example a test operation for the sensors and actuators is then simulated without the vehicle control device  
25 being connected. The control device and the sensor/actuator interface can be supplied by different manufacturers. This makes it possible to break the connection between the sensor and actuator connection and the supplier of the control device. This in turn  
30 permits a modular concept which simplifies the use of replacement parts.

According to the invention a test method is also provided for the device at the end of the line of the  
35 assembly production. Here, the assembly control device (for example engine control or transmission control device) is replaced by a powerful test bench computer and complex tests are carried out at short time

intervals, which tests cannot be performed by an assembly control device owing to limited computing power and limited storage space. The test method can thus be integrated into the line run intervals.

5 Furthermore, the line end test program in the assembly control device can be dispensed with and the program storage requirement thus reduced. Only the test programs for the onboard or running time diagnostics need to be present in the assembly control device.

10

There are various possible ways of advantageously configuring and developing the teaching of the present invention. In this respect, reference is made both to the subordinate claims and to the subsequent  
15 explanation. An embodiment of the simulation device according to the invention is illustrated in the drawing.

20

Fig. 1 shows a representation of a combined engine and transmission controller with two sensor/actuator interfaces according to the invention and two control devices which are each arranged remotely from the assembly, and

25

Fig. 2 shows a representation of a further embodiment of the device according to the invention.

30

The device for controlling an engine 1 and a transmission 2 has, in each case, an engine control device 3 and transmission control device 4 which are arranged remotely therefrom, with the control devices 3, 4 each providing the open-loop and closed-loop control algorithms for the respective assembly. The engine control device 3 is connected in an electrically  
35 conductive fashion to the transmission control device 4 via a vehicle data bus 5, for example a CAN vehicle bus. Messages, which may relate, for example, to information from vehicle-specific sensors 6 or control

signals of the control devices 3, 4 for the actuators 7, are exchanged via the vehicle data bus 5. The engine control device 3 is connected via an assembly data bus 8 to the sensor/actuator interface 9 which is attached to the engine 1. Both the engine control device 3 and the sensor/actuator interface 9 each have a data bus transceiver unit 10 and 11 as interfaces. Via these data bus transceiver units 10, 11, data bus signals are transmitted bidirectionally from the sensor/actuator interface 9 to the engine control device 3 and vice versa.

The digital data bus signals are stored in the sensor/actuator interface 9 and each assigned to the respective engine-mounted sensor 12 or engine-mounted actuator 13. The digital data which is stored in the storage means of the sensor/actuator interface 9 is then subjected, as necessary, to digital/analog conversion and transmitted to the sensors 12 and actuators 13 at and in the engine 1. The sensor/actuator interface 9 only converts the signals of the sensors and actuators 12, 13 into the data bus signals for the assembly data bus 8, and these converted signals of the engine-specific sensors 12 and actuators 13 are then correspondingly converted in the engine control device 3 so that the signals can be processed in the open-loop and closed-loop control algorithm of the engine control device 3 in order to operate the engine 1 at the desired power level or with a desired function.

The transmission control device 4 is arranged remotely from the transmission 2 and is arranged at the automatic selector lever 14 or at a gear speed shift means arranged in the passenger compartment of the vehicle. The transmission control device 4 is arranged, for this purpose, within an encapsulated housing which surrounds the electronics and mechanical components of

the automatic selector lever 14. Otherwise, the transmission control device 4 can be arranged in the vicinity of the automatic selector lever 14. Control signals of the transmission control device 4 are each converted into the data bus signals, and back again into digital signals, in a data bus transceiver unit 15 and in a data bus transceiver unit 16 of the sensor/actuator interface 17. The digital signals are stored in the storage means of the sensor/actuator interface 17 and, where appropriate, converted back again, by means of D/A converters, into signals which can be transmitted via the various connections of the sensor/actuator interface 17 to the transmission-specific sensors 18 and the transmission-specific actuators 19.

The sensor/actuator interface 9 or 17 converts the sensor and actuator signals into the corresponding data bus signals for the assembly data bus 8, 20 and, if appropriate, the value ranges are checked and the signal values are standardized to a specific sensor value range. The actual open-loop and closed-loop control calculations are each carried out in the control devices 3, 4.

The vehicle-specific sensors and actuators 6, 7 may be, for example, operator controls for the engine and transmission, but they can also be telematic functions which have, in whatever form, an influence on the engine and transmission controllers. The calculation functions which are related to the preselection by means of the operator controls are then implemented in the control devices 3, 4 and the complex microelectronics are thus removed from the respective assembly 1, 2. The control devices may be arranged outside the engine compartment, for example in the passenger compartment of the vehicle since the expenditure in terms of cabling for sensors and

actuators is also very low. The assembly data bus 8 and 20 can not only have the signal lines for the sensor signals but also a power or voltage supply line in order to supply the individual sensors and actuators with current. However, the actuators can also be supplied with current independently of the assembly data bus 8, 20.

The transmission controller for the different types of transmission, automated gearshift mechanism, converter transmission or CVT differ primarily with respect to the sensors and actuators. The actual control function for all the transmissions is carried out by means of software modules, with the possibility of each transmission being assigned a specific module and the software being compiled from individual library functions for each transmission. As a result of the invention's arrangement of sensor/actuator interfaces 9, 17 it is also possible to retain the control device hardware in different engine/transmission variants and only the less complex sensor/actuator interface 9, 17 which is embodied as an integrated semiconductor component is replaced.

In another embodiment of the invention according to fig. 2, an assembly data bus 21 which is separate from the vehicle data bus 5 connects a plurality of sensor/actuator interfaces 9, 17, 22, 23 to one another. This permits a uniform exchange of information between the sensor/actuator interfaces 9, 17, 22, 23 and all the assembly control devices 3, 4, 24, 25. This has the advantage that, for example, the transmission control device 3 can directly access the raw value of the engine speed from the sensor/actuator interface 9 on the engine 1 and evaluate, resolve or filter the signal according to transmission-specific requirements. The gateway functionality for such signals, i.e. the expenditure on passing on signals from the assembly



data bus 21 to the vehicle data bus 5 is significantly reduced in the assembly control devices 3, 4, 24, 25.

5 Since all the assembly control devices 3, 4, 24, 25 can then communicate with all the sensor/actuator interfaces 9, 17, 22, 23, if one assembly control device 3, 4, 24, 25 fails the basic functionality can be assumed by another assembly control device 3, 4, 24, 25, for example. If the transmission control device 3  
10 fails the engine control device 4 can make available a basic gearshift program. This means that the arrangement according to the invention results in a control device structure which can be used for redundancy purposes. If redundancy is also necessary at  
15 the sensor/actuator interface 9, 17, 22, 23, the expenditure on the sensor/actuator interface 9, 17, 22, 23 is limited, i.e. it is not necessary for the entire transmission electronics to be configured with redundancy.

20

Figure 2 shows an embodiment with an assembly data bus 21 which connects the individual sensor/actuator interfaces 9, 17, 22, 23 to one another. The assembly data bus 21 is additionally connected to a plurality of  
25 standardized control devices 3, 4, 24, 25 whose hardware is essentially the same and whose differences in terms of their functionality are implemented by means of the closed-loop and open-loop control software. The control devices 3, 4, 24, 25 are each  
30 connected via a uniform data bus transceiver unit 10, 15, 26, 27 to the assembly data bus 21. As has previously been customary in motor vehicles, the control devices 3, 4, 24, 25 are interconnected to one another via the vehicle data bus 5. Each control device  
35 3, 4, 24, 25 can also have an interface 28 where sensors and actuators can be connected directly to the control device 3, 4, 24, 25. This interface 28 is used for sensors/actuators 6, 7 which are arranged near to

the control device 3, 4, 24, 25 and are necessary for each assembly variant so that the interface 28 may be provided in a standardized fashion on all motor vehicle variants.

5

Starter relays, fuel pumps or fuel tank venting valves are either connected directly to a control device or connected via a sensor/actuator interface to a vehicle data bus. The assembly-specific sensors and actuators are connected to the sensor/actuator interface. With respect to the engine, it is also possible to provide sensors such as a knocking sensor, a crankshaft/camshaft rotation speed sensor, an air mass flowmeter and actuators such as throttle valves, swirl valves and exhaust gas valves, ignition coils and injection valves. The sensor/actuator interface is arranged directly on the assembly, i.e. on the transmission or on the engine. The sensors are provided on the outside or inside of the assembly.

20

The sensor/actuator interface is, as it were, a distributor between the various sensors and actuators and converts the sensed signals into data bus signals so that the signals can be transmitted via the data bus sequentially, i.e. using a time-division multiplex method, or in parallel in a frequency-division multiplex method. Apart from the sensing of signals and the operation of actuators, the sensor/actuator interface can also carry out preprocessing of signals and storage of adaptation parameters. However, the sensor/actuator interface does not carry out any open-loop/closed-loop control algorithm calculations but instead merely transmits the sensor and actuator signals via the assembly data bus to the control device which is arranged remotely where the complex control algorithms are carried out.

35

The major advantage of the present invention is that

only the sensor/actuator interface has to be adapted for different assembly variants, for example petrol or diesel engines with different numbers of cylinders, different transmissions with different gear speeds and  
5 differing clutches. The remotely arranged control device can remain essentially unchanged in terms of its hardware, while all that is necessary is to input other software modules into the control device.

10 When there are a greater number of sensors, a sensor/actuator interface with a greater number of connections is then provided, with the data bus protocol remaining unchanged so that only a greater  
15 number of messages are transmitted via the assembly data bus. As a result, one standard control device can be provided for a predefined number of assembly variants. In the field of motor vehicle manufacture or aircraft manufacture this gives rise to the  
20 considerable advantage that it is not necessary to produce a new control device for each assembly variant. Only the sensor/actuator interface, as it were the adaptor or multiple plug, for the sensors and actuators is changed. The complex microcomputers with the  
25 closed-loop and open-loop control algorithms are not provided in the sensor/actuator interface and accordingly also do not need to be adapted with a high degree of expenditure.

As a result of the separation of the control device as  
30 a closed-loop and open-loop control unit and the sensor/actuator interface for the assembly-specific sensor system and actuator system it is possible for the control device with the highly integrated  
semiconductors such as microcomputers and memories to  
35 be located in the vehicle at an installation location which is loaded less in terms of environmental influences, for example in the footwell of the front seat passenger. As a result, with the highly integrated

semiconductors there are cost and quality advantages over the current solution where a control device with microcomputer is installed directly on the assembly.

5 The sensor/actuator interface can be configured easily, in terms of cost and quality criteria, for the rough operating conditions in the engine compartment and on the assembly. The sensor/actuator interface can be embodied with a small number of printed circuit board  
10 layers, simpler ceramic substrates such as thick-film ceramic,  $Al_2O_3$  and less complex modules than is the case with the control devices used on the assembly in the past. The smaller complexity of the sensor/actuator interface permits the dissipated heat to be conducted  
15 away better, in particular from the power semiconductors and makes higher permissible operating temperatures possible as well as providing improved robustness with respect to environmental influences. Furthermore, a small number of sensors and actuators  
20 can already be integrated in the sensor/actuator interface. As a result of the greater degree of robustness of the sensor/actuator interface in comparison with a control unit, more free spaces are obtained when locating the sensors and actuators on the  
25 assembly itself. The sensor/actuator interface can therefore be used for optimized placing with respect to the assembly cable set.

The sensor/actuator interface has a storage means in  
30 which the digital sensor signals can be buffered and where the sensor signals are converted in terms of the predefined value range and/or standardization of the signals to a predefined numerical range, the data bus transceiver unit reading out the digital sensor signals  
35 from the storage means and converting them into data bus signals which can then be transmitted to the control device via the assembly data bus. The conversion into the data bus signals at the

sensor/actuator interface can be carried out, for example, into the known data bus protocols, for example CAN, LIN, Firewire, Bluetooth, USB, pulse width modulation and also other modulated signals such as frequency modulation or amplitude modulation. In order to convert into the predefined value range and in order to diagnose whether the sensor or actuator carries out its functions it is possible to provide a very small robust microcomputer so that when the control device fails or when there are interface problems the safety and availability of the sensor and actuator signal transmission is then ensured, for example, by means of an emergency transmission path. However, the sensor/actuator interface also differs from the control devices provided in the fitting solution in that no open-loop and closed-loop control algorithms are provided for the sensors and actuators. A pure hardware solution can be provided for a particularly fast conversion of the sensor signals into data bus signals.

In one particularly preferred development of the sensor/actuator interface for production vehicles such as ships, aircraft and motor vehicles, there are at least two embodiments of each type, each differing in the number of sensor/actuator connections provided. In certain production vehicles it is not necessary for all the connections of the sensor/actuator interface to be assigned but instead the sensor/actuator interface is configured in such a way that it can be used even when certain connections are not assigned. As a result a very small number of variants of the sensor/actuator interface and of the associated control devices is produced even though there can be a large number of different assembly variants. It is then not necessary to provide new connections for new sensors and actuators on the control device every time but instead only one data bus connection to the sensor/actuator interface for each variant. The number of variants

ultimately affects the data bus messages to be transmitted. The individual sensor signals are usually transmitted sequentially by means of an asynchronous or synchronous data bus protocol to the control device and  
5 evaluated there in their chronological sequence. The closed-loop control algorithms are then applied by the control device and the control signals for the actuators are transmitted again via the assembly data bus to the sensor/actuator interface and converted  
10 there in such a way that the actuators can be actuated.

It is also possible to switch a plurality of sensor/actuator interfaces in parallel or in cascades so that one sensor/actuator interface can be arranged  
15 on the engine and one sensor/actuator interface can be arranged on the transmission. The control device can then have, for example, two data bus connections which are connected in an electrically conductive fashion to the different sensor/actuator interfaces.

20 In another development of the invention, the transmission control device is integrated into the housing of the automatic transmission or gear speed selector lever of the means of transportation. If  
25 appropriate, the entire transmission control system including a sensor/actuator interface can be integrated into the selector lever. This makes sense in particular in rear-wheel drive vehicles because of the direct proximity of the transmission and gear selector lever.

30 The control apparatus can also be arranged in conjunction with assemblies such as clutches, starter generators or drives in the field of utility vehicle engineering, marine engineering or aircraft  
35 engineering. In addition, according to the present invention the sensor/actuator interface can also be used in hybrid vehicles or hydrogen-powered vehicles.

A further advantage of the present invention is that a diagnosis or test phase, for example during the manufacture of vehicles, is simplified. Instead of connecting the sensor/actuator interface to the control device it can be connected directly to a diagnostic device or test device which models the control device in various test phases. In particular, workshop and test bench computers may be connected to the production line to the sensor/actuator interfaces or to the assembly data bus. Alternatively, what is referred to as a hardware-in-the-loop method can be carried out. The sensor/actuator interface permits simple connection of the test devices which then make available the necessary test signals for the test operation. For example a test operation for the sensors and actuators is then simulated without the vehicle control device being connected. The control device and the sensor/actuator interface can be supplied by different manufacturers. This makes it possible to break the connection between the sensor and actuator connection and the supplier of the control device. This in turn permits a modular concept which simplifies the use of replacement parts.

According to the invention a test method is also provided for the device at the end of the line of the assembly production. Here, the assembly control device (for example engine control or transmission control device) is replaced by a powerful test bench computer and complex tests are carried out at short time intervals, which tests cannot be performed by an assembly control device owing to limited computing power and limited storage space. The test method can thus be integrated into the line run intervals.

Furthermore, the line end test program in the assembly control device can be dispensed with and the program storage requirement thus reduced. Only the test programs for the onboard or running time diagnostics

need to be present in the assembly control device.

There are various possible ways of advantageously configuring and developing the teaching of the present invention. In this respect, reference is made both to the subordinate claims and to the subsequent explanation. An embodiment of the simulation device according to the invention is illustrated in the drawing.

10

Fig. 3 shows a representation of a combined engine and transmission controller with two sensor/actuator interfaces according to the invention and two control devices which are each arranged remotely from the assembly, and

15

Fig. 4 shows a representation of a further embodiment of the device according to the invention.

20 The device for controlling an engine 1 and a transmission 2 has, in each case, an engine control device 3 and transmission control device 4 which are arranged remotely therefrom, with the control devices 3, 4 each providing the open-loop and closed-loop control algorithms for the respective assembly. The engine control device 3 is connected in an electrically conductive fashion to the transmission control device 4 via a vehicle data bus 5, for example a CAN vehicle bus. Messages, which may relate, for example, to information from vehicle-specific sensors 6 or control signals of the control devices 3, 4 for the actuators 7, are exchanged via the vehicle data bus 5. The engine control device 3 is connected via an assembly data bus 8 to the sensor/actuator interface 9 which is attached to the engine 1. Both the engine control device 3 and the sensor/actuator interface 9 each have a data bus transceiver unit 10 and 11 as interfaces. Via these data bus transceiver units 10, 11, data bus signals are

30

35



REPLACEMENT  
ART 34/1987

transmitted bidirectionally from the sensor/actuator interface 9 to the engine control device 3 and vice versa.

5 The digital data bus signals are stored in the sensor/actuator interface 9 and each assigned to the respective engine-mounted sensor 12 or engine-mounted actuator 13. The digital data which is stored in the storage means of the sensor/actuator interface 9 is  
10 then subjected, as necessary, to digital/analog conversion and transmitted to the sensors 12 and actuators 13 at and in the engine 1. The sensor/actuator interface 9 only converts the signals of the sensors and actuators 12, 13 into the data bus  
15 signals for the assembly data bus 8, and these converted signals of the engine-specific sensors 12 and actuators 13 are then correspondingly converted in the engine control device 3 so that the signals can be processed in the open-loop and closed-loop control  
20 algorithm of the engine control device 3 in order to operate the engine 1 at the desired power level or with a desired function.

The transmission control device 4 is arranged remotely  
25 from the transmission 2 and is arranged at the automatic selector lever 14 or at a gear speed shift means arranged in the passenger compartment of the vehicle. The transmission control device 4 is arranged, for this purpose, within an encapsulated housing which  
30 surrounds the electronics and mechanical components of the automatic selector lever 14. Otherwise, the transmission control device 4 can be arranged in the vicinity of the automatic selector lever 14. Control signals of the transmission control device 4 are each  
35 converted into the data bus signals, and back again into digital signals, in a data bus transceiver unit 15 and in a data bus transceiver unit 16 of the sensor/actuator interface 17. The digital signals are

stored in the storage means of the sensor/actuator interface 17 and, where appropriate, converted back again, by means of D/A converters, into signals which can be transmitted via the various connections of the sensor/actuator interface 17 to the transmission-specific sensors 18 and the transmission/specific actuators 19.

The sensor/actuator interface 9 or 17 converts the sensor and actuator signals into the corresponding data bus signals for the assembly data bus 8, 20 and, if appropriate, the value ranges are checked and the signal values are standardized to a specific sensor value range. The actual open-loop and closed-loop control calculations are each carried out in the control devices 3, 4.

The vehicle-specific sensors and actuators 6, 7 may be, for example, operator controls for the engine and transmission, but they can also be telematic functions which have, in whatever form, an influence on the engine and transmission controllers. The calculation functions which are related to the preselection by means of the operator controls are then implemented in the control devices 3, 4 and the complex microelectronics are thus removed from the respective assembly 1, 2. The control devices may be arranged outside the engine compartment, for example in the passenger compartment of the vehicle since the expenditure in terms of cabling for sensors and actuators is also very low. The assembly data bus 8 and 20 can not only have the signal lines for the sensor signals but also a power or voltage supply line in order to supply the individual sensors and actuators with current. However, the actuators can also be supplied with current independently of the assembly data bus 8, 20.

The transmission controller for the different types of transmission, automated gearshift mechanism, converter transmission or CVT differ primarily with respect to the sensors and actuators. The actual control function  
5 for all the transmissions is carried out by means of software modules, with the possibility of each transmission being assigned a specific module and the software being compiled from individual library functions for each transmission. As a result of the  
10 invention's arrangement of sensor/actuator interfaces 9, 17 it is also possible to retain the control device hardware in different engine/transmission variants and only the less complex sensor/actuator interface 9, 17 which is embodied as an integrated semiconductor  
15 component is replaced.

In another embodiment of the invention according to fig. 2, an assembly data bus 21 which is separate from the vehicle data bus 5 connects a plurality of  
20 sensor/actuator interfaces 9, 17, 22, 23 to one another. This permits a uniform exchange of information between the sensor/actuator interfaces 9, 17, 22, 23 and all the assembly control devices 3, 4, 24, 25. This has the advantage that, for example, the transmission  
25 control device 3 can directly access the raw value of the engine speed from the sensor/actuator interface 9 on the engine 1 and evaluate, resolve or filter the signal according to transmission-specific requirements. The gateway functionality for such signals, i.e. the  
30 expenditure on passing on signals from the assembly data bus 21 to the vehicle data bus 5 is significantly reduced in the assembly control devices 3, 4, 24, 25.

Since all the assembly control devices 3, 4, 24, 25 can  
35 then communicate with all the sensor/actuator interfaces 9, 17, 22, 23, if one assembly control device 3, 4, 24, 25 fails the basic functionality can be assumed by another assembly control device 3, 4, 24,

25, for example. If the transmission control device 3 fails the engine control device 4 can make available a basic gearshift program. This means that the arrangement according to the invention results in a control device structure which can be used for redundancy purposes. If redundancy is also necessary at the sensor/actuator interface 9, 17, 22, 23, the expenditure on the sensor/actuator interface 9, 17, 22, 23 is limited, i.e. it is not necessary for the entire transmission electronics to be configured with redundancy.

Figure 2 shows an embodiment with an assembly data bus 21 which connects the individual sensor/actuator interfaces 9, 17, 22, 23 to one another. The assembly data bus 21 is additionally connected to a plurality of standardized control devices 3, 4, 24, 25 whose hardware is essentially the same and whose differences in terms of their functionality are implemented by means of the closed-loop and open-loop control software. The control devices 3, 4, 24, 25 are each connected via a uniform data bus transceiver unit 10, 15, 26, 27 to the assembly data bus 21. As has previously been customary in motor vehicles, the control devices 3, 4, 24, 25 are interconnected to one another via the vehicle data bus 5. Each control device 3, 4, 24, 25 can also have an interface 28 where sensors and actuators can be connected directly to the control device 3, 4, 24, 25. This interface 28 is used for sensors/actuators 6, 7 which are arranged near to the control device 3, 4, 24, 25 and are necessary for each assembly variant so that the interface 28 may be provided in a standardized fashion on all motor vehicle variants.

REPLACED BY  
ART 31.5.1DaimlerChrysler AG  
StuttgartPatent Claims

5  
1. A device for controlling an engine (1) and/or  
transmission (2) having a control device (3, 4, 24, 25)  
which is arranged remotely from the engine/transmission  
(1, 2) and which provides the open-loop and closed-loop  
10 control algorithms, and a unit which is electrically  
conductively connected directly to a plurality of  
sensors (12, 18) and which is attached to the  
engine/transmission (1, 2), wherein the unit has an A/D  
converter for converting the sensor signals originating  
15 from the sensors (12, 18) into digital sensor signals,  
and the digital sensor signals are converted into data  
bus signals by means of a signal converter and fed into  
a data bus (5) by means of a data bus transceiver unit  
(10, 11, 15, 16) in order to be able to communicate via  
20 the data bus (5) between the unit and the control  
device (3, 4, 24, 25) which is arranged remotely  
therefrom, characterized in that a plurality of control  
devices (3, 4, 24, 25) are embodied with a uniform data  
bus transceiver unit (10, 11, 15, 16) to each of which  
25 an assembly data bus (8, 20, 21) is connected, in that  
the unit is embodied as an assembly-specific  
sensor/actuator interface (9, 17, 22, 23) with a  
plurality of parallel connections for the sensors (12,  
18) and a connection for the assembly data bus (8, 20,  
30 21), in that a signal converter is provided for  
converting the digital sensor signals of a plurality of  
sensors (12, 18) into the data bus signal so that in  
embodiments of the device for different assembly  
variants with different sensors (12, 18) the same  
35 control device (3, 4, 24, 25) can be used without  
hardware modification of its sensor connection, in that  
the signal converter converts the sensor signals  
directly into the data bus signals without intermediate

REPLACED BY  
ART 34 AMDT

connection of a calculating means corresponding to an open-loop/closed-loop control algorithm, and in that the sensor/actuator interface (9, 17, 22, 23) is designed for series traffic means with a plurality of engine/transmission variants in at least two embodiments which differ in the number of sensor connections provided.

2. The device as claimed in claim 1, characterized in that actuators (13, 19) can be additionally connected to the sensor/actuator interface (9, 17, 22, 23), wherein the control data which is input via the assembly data bus (8, 20, 21), for the actuator or actuators (13, 19) is converted into digital control data for the individual actuator (13 or 19) so that the actuators (13, 19) can be actuated via the assigned sensor/actuator connections.

3. The device as claimed in claim 1, characterized in that the sensor/actuator interface (9, 17, 22, 23) carries out checking of the sensor signals with respect to the predefined value range and/or standardization of the signals to a predefined numerical range.

4. The device as claimed in claim 1 or 2, characterized in that the sensor/actuator interface (9, 17, 22, 23) has a storage means in which the digital sensor signals can be buffered, and in that the data bus transceiver unit (10, 11, 15, 16) can read out the digital sensor signals from the storage means and converts them into data bus signals.

5. The device as claimed in one of claims 1 to 4, characterized in that the same data bus protocol is provided for use with a plurality of different embodiments of the device with a different number of sensors/actuators (12, 13, 18, 19) in comparison with the control device (3, 4, 24, 25) which is arranged

remotely.

6. The device as claimed in one of claims 1 to 5,  
characterized in that for certain production vehicles  
5 some of the sensor/actuator connections of the  
sensor/actuator interface (9, 17, 22, 23) are not  
assigned.